

## Plenum Slot Diffusers Nova Series • Supply

**Models:**

- N-1 • 3/4" Slot
- N-4 • 3/8" Slot

Model	Inlet Sizes Available	C	F	Nominal Length L
N-1	6, 8, 10	3/4	3/4	24, 36, 48,
N-4	6, 8, 10	3/8	1 1/4	60

Note: 24" length available in 6" and 8" inlets only.

Inlet Size	D	E
6	7 9/16	3
8	10 1/16	4
10	13 1/4	4

Dimensions are in inches.

**Accessories (optional)**

Check  if provided.

- External Insulation

Optional Slot Diffuser Plaster Frame

- PF-N

Ceiling Opening:  
Length = Nominal Length L plus 1/2"  
Width = Plenum Width plus 3/4"

The PF-N diffuser mounting frame can be used in sheetrock or plaster ceiling. The frame is mounted in the ceiling by others. The Model N-1/N-4 diffuser is mounted on the inside lip of the frame. Plaster frame is 1 1/2" in height.

**Standard Finish: #84 Black**

### General Description

- TITUS Nova Series high induction N-slot diffusers are excellent for variable volume applications.
- Designed for both heating and cooling.
- For use in standard lay-in ceiling systems.
- Choice of 3/4" or 3/8" supply slot.
- Standard lengths are 24", 36", 48" and 60".
- Material is steel.

This submittal is meant to demonstrate general dimensions of this product. The drawings are not meant to detail every aspect of the product. Drawings are not to scale. Titus reserves the right to make changes without written notice.